

KELI CEE
CENTRAL & EASTERN EUROPE

KELI

Keli Electric Manufacturing(Ningbo)Co.,Ltd.

ZSF–A/–ASS/ZSFY–A/–ASS Loadcell


ZSF–A/–ASS/ZSFY–A/–ASS

RoHS

OIML

OIML







Truck scale,railway scale, axle-load scale,floor scale

TECHNICAL PARAMETER|

4Wires:Exc+(Red);Exc-(Black);Sig+(Green);Sig-(White)

Rated capacities(Emax)	10,15,20,25,30,40,50t	Temperature range, compensated	–10℃~+40℃
Sensitivity	2.0±0.002mV/V	Temperature range, operating	-30~+70℃
Total error	C2~C5	Maximum safe overload	150%F.S
Creep error (30min)		Ultimate overload	250%F.S
Zero balance	±1%F.S	Excitation,recommended	10~12V DC
TC ZERO	±0.02%F.S/10℃	Excitation,maximum	15V DC
TC SPAN	±0.02%F.S/10℃	Protection class	IP68
Input resistance	400±20Ω(ZSF),700±20Ω(ZSFY)	Construction	Alloy Steel Stainless Steel
Output resistance	352±3Ω；352±5Ω（L≥15m)(ZSF),706±7Ω(ZSFY)	Cable	Length:8m(10t),10m(15t),12m(20~25t),14m(30t),16m(40~50t)
Insulation resistance	≥5000MΩ		Diameter: ϕ5mm


Keli CEE
ul. Zółkiewskiego 3A, 4 piętro
63-400 Ostrow Wielkopolski
tel./fax. +48 62 592 42 78
e-mail: info@keli-cee.pl
www.keli-cee.pl





Keli Electric Manufacturing(Ningbo)Co.,Ltd.

ZSF–A/ZSFY–A Weighing module

ZSF–A/ZSFY–A







Keli CEE
ul. Zółkiewskiego 3A, 4 piętro
63-400 Ostrow Wielkopolski
tel./fax. +48 62 592 42 78
e-mail: info@keli-cee.pl
www.keli-cee.pl